

Cement Tiles Collection



ELISAPASSINOSTUDIO.

---

Cement Tiles Collection



Our Cement Tiles are, as in the past, hand-produced one by one. Made from an ingenious combination of marble powder, Portland cement, water, sand and natural mineral pigments, these tiles are environmentally friendly and sustainable, just like many centuries ago. No heating is involved during the production as the tiles are not kiln-fired, but left to dry in fresh air for 21 to 28 days.

## 9 DESIGN | 24 COLOURS

COLLECTION	P. 04
COLOUR PALETTE	P. 05
COLOR COMBINATIONS	P. 07
PATTERNS	P. 08
INSTALLATION AND MAINTENANCE	P. 11
FREQUENTLY ASKED QUESTIONS	P. 13
TERMS AND CONDITIONS	P. 15
FURTHER INFORMATION	P. 17
CONTACTS	P. 19

Our Cement Tiles are characterized by its particular colour shading, matte finish, smooth texture and countless combinations.



CENTINA



ABACO



ARCO



CAPITELLO



OBELISCO



LUNETTA



ABSIDE



AGORA



ESEDRA

**Suitability** Walls, floors, kitchens, bathrooms, showers, swimming pools, facades

**Size** 20x20 cm

**Thickness** 1,5 cm

**Tiles per square mt.** 25 tiles

---

## Colour Palette


## Cement Tiles




C001 | PURE WHITE



C050 | STUDIO WHITE



C003 | SO MASCARPONE



C052 | MOCASSIN MUST



C023 | SUPER GOJI



C022 | CORAL CURRY



C021 | ORANGE SPICE



C033 | ANTIQUE ROSE



C026 | DELICATE PINK



C025 | JUST ROSE



C020 | PEACHY PINK



C030 | ROSY QUARTZ



C035 | CRYSTAL BLUE



C043 | BLUE CLOUDS



C017 | MELLOW YELLOW



C018 | SUNSHINE YELLOW



C037 | BAHAMAS TEAL



C007 | SCUBA DIVE



C006 | BORA BORA



C005 | PARADISE SOUL



C041 | MINERAL WHITE



C045 | ICEBERG MINT




C010 | GREEN MARTINI



C042 | FRENCH BLUE

OBELISCO



OBE.001C



OBE.002C




OBE.003C



OBE.004C


CENTINA




CEN.001C



CEN.002C




CEN.003C




CEN.004C

LUNETTA



LUN.001C



LUN.002C



LUN.003C



LUN.004C

ESEDRA



ESE.001C



ESE.002C



ESE.003C




ESE.004C


CAPITELLO




CAP.001C



CAP.002C



CAP.003C




CAP.004C

ABSIDE



ABS.001C



ABS.002C




ABS.003C



ABS.004C


AGORA



AGO.001C



AGO.002C



AGO.003C



AGO.004C

ARCO



ARC.001C



ARC.002C




ARC.003C



ARC.004C


ABACO



ABA.001C



ABA.002C



ABA.003C




ABA.004C


Tile Size: 20x20x1,5cm | Tiles per square meter: 25  
 There may be some variation in the colours of the actual product  
 Drawings not to scale. Tiles are handmade, shade variation can be expected.

# Patterns


# Cement Tiles




**6000.A**  
*Centina*




**6008.B**  
*Esedra*




**6003.A**  
*Obelisco*




**6000.B**  
*Centina*




**6008.A**  
*Esedra*




**6003.B**  
*Obelisco*




**6000.C**  
*Centina*




**6008.D**  
*Esedra*




**6003.C**  
*Obelisco*



**6000.D**  
*Centina*




**6008.C**  
*Esedra*




**6003.D**  
*Obelisco*

# Patterns


# Cement Tiles




**6006.A**  
*Agora*




**6005.D**  
*Lunetta*




**6002.C**  
*Arco*



**6006.B**  
*Agora*




**6005.C**  
*Lunetta*




**6002.D**  
*Arco*



**6006.D**  
*Agora*




**6005.B**  
*Lunetta*




**6002.B**  
*Arco*



**6006.C**  
*Agora*




**6005.A**  
*Lunetta*




**6002.A**  
*Arco*

# Patterns


# Cement Tiles




**6007.C**  
Abside




**6004.D**  
Capitello




**6001.A**  
Abaco




**6007.B**  
Abside




**6004.A**  
Capitello




**6001.B**  
Abaco




**6007.A**  
Abside




**6004.B**  
Capitello




**6001.C**  
Abaco



**6007.D**  
Abside



**6004.C**  
Capitello



**6001.D**  
Abaco

Please note these tips are guides only and should be used in addition to the relevant industry standards for encaustic cement tiles. Note that installation may vary from site to site with varying conditions experienced on site. The contractor and specifier should decide if these suggestions are suitable for their application or require further adjustment.

### TILE UNDERSTANDING

Shade variation: These are hand-crafted products and so there will, of course, be some variations in colour tone and natural character that make them unique. Shade variation is inherent in encaustic cement tiles and certain tiles will show greater variation within their lots.

### TILE PREPARATION

Meticulously plan your layout. The time you take for preparation and placement will greatly impact the finished result.

- Prior to the installation allow tiles to season in their final environment.
- Pre-sort your tiles so you can distribute the range of variation throughout the installation.
- Blending is recommended.
- Inspect each tile deformities that make its use inappropriate for the application intended.
- Both sides of the tiles should be wiped cleaned of any dust before installation.
- The tiles can be cut using a diamond-blade (ideally a water-cooled machine).

OPTIONAL: Before installation, once the tiles are perfectly dust cleaned apply two coats of an impregnating sealant with a wide brush or roller.

### TILE LAYING

Proper substrate preparation and the right choice of adhesives and grouts for the type of tile and specific project conditions are critical for achieving a long-lasting installation.

Laying General Methods:

1. Prepare the surface. Cement tiles must be installed on a well leveled, clean and dry surface. Humid subsoil will cause fur deposits on the tile's surface.
2. Determine the layout and mark the surface. For aesthetic and technical optimisation, define starting points and cuttings.

3. Apply the proper tile adhesive. Use a large-toothed trowel to spread the adhesive.

4. Back butter tiles. Apply adhesive on the back of the tile using a large-toothed trowel.

5. Install the tiles. Lay the tiles and press into place using your hands leaving a thin gap (1 or 2 mm) for the joint.

Ensure tiles are completely level throughout the installation, as unevenness cannot be rectified later.

### TILE SURFACE PREPARATION BEFORE SEALING AND GROUTING

Once the adhesive dry, clean the surface by scrubbing it using a diluted solution of alkaline cleaner and rinse with warm water. It will remove any dust and dirt that may have accumulated during the installation process, eliminating as well the thin layer of pigmented dust that can still cover the tiles.

Tiles should then be allowed to set for 24 hours before applying sealant and grout.

### TILE SEALING BEFORE GROUTING

An impregnating sealing is an essential step in protecting the beauty and ensuring the longevity of cement tiles, as it accentuates the appearance and helps to protect against fading and staining. The sealant is a solvent based liquid that limits water and oil penetration. It impregnates the tile, protects it and keeps its natural matt aspect.

Apply with a brush or a roller on a dry and clean surface. This should be applied in successive applications until the tile is fully saturated. Saturation has been achieved when an even layer of sealant is still visible on the surface after 30 minutes.

Do not apply too much. The excess would leave glistening stains on the surface (brush traces).

Always try the sealer on a loose tile before applying it on the entire surface in order to measure the grade of absorption of the tiles.

## TILE GROUTING

It is recommended to use a non-pigmented, exible, cementitious grout compound suitable for the application of cement tiles. Pigments from the joint might stain the tiles irreversibly.

Grouting General Methods:

1. Seal the tiles. Always ensure that surfaces are properly sealed before grouting.

In order to prevent the soiling or staining, a proper sealant must be applied, so that the grout residues do not get deeply adhered to the tiles layer of pigments and these can be removed easily.

2. Grout the joints. Fill the gap between the tiles using a spatula, without spreading the grout on tiles.

3. Remove excess. Clean the excess grout immediately, using a damp cloth. Do not use chemical cleaners.

4. Clean the floor. Remove any cement residue stains immediately, using a pH neutral cleaner.

Never use cement remover, strong detergents or bleach as these will damage the tiles. Stains or spots can be delicately removed with a scouring pad or fine-grained sandpaper.

## FINISHING AFTER GROUTING

The finishing completes the protection against wear and dirt.

Always apply a final coat of impregnating sealant making sure to cover the grout joints as well.

Further to the above you can also apply a surface wax. This will offer extra protection and give an attractive patina.

For larger surfaces or high traffic floor (bars, restaurants and other public spaces), a special protection and attention on a daily maintenance is recommended. Using a polishing machine may accelerate the process and protect the entire floor evenly.

## MAINTENANCE

Keep the surface as free as possible of loose dust and grit with regular vacuuming or sweeping. This will reduce the sandpaper effect of dirt getting compacted into the surface and joints.

Wash the floor using a pH neutral cleaner (ideally biodegradable and environment friendly) to remove the dirt that a vacuum won't pick up and for hygiene purposes.

We strongly recommend avoiding the use of bleach based cleaners, washing-up liquids or any other acid cleaners.

Need more information? Contact us!

## All you need to know about our Cement Tiles Collection

### PRODUCT UNDERSTANDING

#### \_ARE CEMENT TILES A GREEN MATERIAL?

Cement Tiles are truly a green material. During the production of cement tiles no heating is involved, as the tiles are not kiln-fired but left to dry in fresh air for 21 to 28 days and the materials used are environmentally friendly and sustainable, just like many centuries ago. That's why more and more professional designers and consumers like to use cement tiles as a high quality and decorative element.

#### \_WHAT EXACTLY IS THE CEMENT TILE CURE?

After pressing, encaustic cement tiles are soaked in water to ensure proper hydration for curing. Like structural concrete, cement tiles cures and hardens chemically over time. It is not that the cement dries, but that it goes through hydration and carbonation (chemical reactions that converts the calcium oxide in the Portland cement to calcium hydroxide, and eventually calcium carbonate). It takes about 4 weeks for the cement to reach 90% of its potential strength, and it will continue to gain strength for decades.

#### \_DO COLOURS VARY OVER TIME?

The tile colour will change slightly as the cement cures, and will be affected again when sealed. Tiles may also fade in the sunlight and rain.

### BESPOKE & CUSTOMISATION

#### \_CAN I CUSTOMISE A PRODUCT?

Yes, we are happy to produce custom colours and sizes to best fit your project, although there are limitations to what we can achieve in concrete.

### PLACING AN ORDER

#### \_CAN I BUY ONLINE?

We are not prepared to sell directly through our

website. For ordering tiles, custom requests, pricing, lead times or other needs please email or call us so one of our Design Consultants can offer personal assistance.

#### \_DO YOU SHIP INTERNATIONALLY?

We have successfully supplied tiles for projects all over the world. We are happy to provide a shipping quote for international orders.

#### \_DO YOU HAVE ANY TILES IN STOCK?

Although we mainly produce to order, we might have a selection of stock available. Please contact us to know about the stock.

#### \_CAN I GET SAMPLES?

Yes, we understand the importance of coordinating all the elements for your project and are happy to provide samples during your selection process.

#### \_ARE THERE ANY MINIMUM ORDER QUANTITIES? DO YOU CHARGE A SET-UP FEE FOR SMALLER ORDERS?

There is a 3 sqm minimum order per reference. Because each order is custom made, a set-up procedure is required.

#### \_SHOULD I ORDER EXTRA TILES?

Yes, we advise a 10% contingency on top of the minimum quantity needed. This overage allows for the possibility of breakage during installation, for greater range selection and extras in case of damage in the future. Always refer to your installer when determining quantities.

#### \_CAN I RETURN MY TILES?

Because we make our tiles specially for you, returns are not accepted unless they are defective or damaged in shipping.

### \_ONCE AN ORDER IS PLACED CAN I CHANGE IT?

Because each order is custom made, we cannot change it once it has gone into production. If you do have a change, please contact us immediately to see if we can help resolve the matter quickly.

### \_WHAT WOULD BE THE MINIMUM LEAD TIME FOR EMERGENCY ORDERS?

If you need materials sooner for a rush order or job completion, please call and ask for a lead time specifically for you. Although we keep a limited quantity of our most popular products on hand, we operate on a first come first served policy without discrimination. When your order is placed check with us what is the estimated lead time.

## INSTALLATION & MAINTENANCE

### \_CAN CEMENT TILES BE INSTALLED OUTDOORS?

There are several considerations in regards exterior using of Cement Tiles. First, tiles may experience some cracking if installed in an environment with freeze conditions. A second consideration for outdoor installations is sun exposure. The tile colour may diminish with UV exposure, especially blue and green pigments. Furthermore, if you want to keep a glossy, perfect finish, we do not generally recommend them for outdoor use.

### \_CAN I INSTALL YOUR TILES ON THE KITCHEN BACKSPLASH?

Yes, certainly. As with any installation, however, they should be well sealed to prevent staining.

### \_CAN CEMENT TILES BE USED WITH RADIANT HEAT FLOORS?

Yes, cement tiles have excellent thermal mass and are sublime with a radiant heat floor. When installing over radiant heat, we suggest a larger grout joint (3-4 mm) instead of the small grout joint (1-2 mm) we normally recommend. Also, the grout material should be flexible. This will allow for some natural expansion/contraction of the heated floor without cracking the tiles.

### \_WHAT SIZE DO YOU SUGGEST FOR GROUT SPACING?

Our Cement Tiles are sized to accommodate a 1 to 2 mm grout space, a much tighter grout joint than is typical with ceramic tiles, so the visual effect is more like a carpet.

Many factors determine the size of a grout joint. It is important to discuss it with both your architect and installer.

### \_ARE YOUR CEMENT TILES PRE-SEALED?

We always send our tiles in a natural state, therefore they must be always sealed upon installation. When needed, the necessary treatment products can be sent along with the material but they would have to be applied on site.

### \_DO I NEED TO SEAL THE CEMENT TILES?

Yes. Sealing is essential to protecting the beauty and ensuring the longevity of any cement tiles.

### \_WILL THE TILE BE STAINED BY WINE OR ACIDS?

If it is correctly sealed, it will not absorb stains. Soda, wine, acids, etc. should not be left to sit on the tile as they will eventually eat through the sealer and stain the tile.

### \_HOW DO I MAINTAIN MY CEMENT TILES?

The tiles should be cleaned with pH-neutral soap and water. Do not use any acids or bleach on these tiles. If sealed with a topical sealant, they may need to be resealed every couple of years.

All our products are shipped worldwide

## PLACING ORDERS

Please order carefully.

- Check the product specification. Samples may be requested.
- Check the quantities. Ordering proper quantities is essential, as we cannot guarantee an exact match between batches. We recommend ordering 10% extra tiles.
- Check delivery requirements and delivery costs.
- Once production has begun, orders cannot be cancelled.
- There is a 3 sqm minimum order per reference.

## PRICES

- Prices are subject to change without notice according to cost variations.
- All product prices quoted exclude the cost of delivery and taxes.
- VAT rate is 23%.

## DELIVERY

- We can arrange delivery anywhere in the world. Please contact us to request a freight quote.
- Tiles are packed in cardboard boxes, loaded on a protected and sealed pallet. Pallets are delivered on the pavement. • Freight quotes are passed on at cost with a 15 Euro pallet charge per pallet used.
- Delivery terms are to be considered indicative. Eventual delivery delays do not entitle customers to claim indemnity.

## PAYMENT TERMS

- A 50% deposit is required to confirm your order.
- The balance is due before order released. The goods will be released immediately after the payment has been received and cleared in full.

## LEAD TIMES

Nearly every Cement Tiles product is made to order. Our lead times vary from product to product and may also be extended at certain times of the year. Nevertheless, we try to follow these timelines:

- In-stock tiles: 1 week to ship.
- Made to order tiles: 6 weeks to ship.
- Exceptionally large quantities: quoted on an individual basis.

All lead times will be quoted on purchase order. Please contact us for stock checks.

## TOLERANCE TO DIMENSIONS AND SHADES

- Tiles are referred to its nominal size, not its actual size. Due to the handcrafted nature of our products, dimensions are approximate and may be subject to a degree of inaccuracy.
- A possible variation in shades is considered as a particularity of such products. Tiles may exhibit variations from samples and within a shipped lot.

### CUSTOM PROJECTS

Please inquire us about custom developments.

- Custom projects are priced accordingly.
- Custom sizes, patterns and colours are available for an additional charge.

### RETURNS

Please order carefully as we cannot accept returns. Please check your products carefully on delivery.

- Any problems with quality, quantity and kind of material supplied must be reported to us within 7 working days of receipt of the order.
- In case of claim the buyer should put the disputed material at our disposal for any defect checking. No claim will be accepted once the material has been installed.
- Damage caused by inappropriate installation, accident, misuse or improper maintenance is not covered by our products warranty.
- Variations in colour, shade and tonality are inherent characteristics our Cement Tiles and are not defects.
- Variations in facial dimensions and thickness will be allowed as per handmade products standards.
- Although we provide Installation and Maintenance guidelines, its liability is strictly limited to the supply of products.

Need more info? Contact us at [hello@elisapassino.com](mailto:hello@elisapassino.com)

*All the content of the pages on this catalogue and on the website (including pictures, logos, photographs, copies and other materials) represent the copyright of Elisa Passino.*

*For further information about the collection, Terms and Conditions, Installation and Maintenance, please visit our website:*

**[elisapassino.com](http://elisapassino.com)**

Technical Features	Standards	Test Results	Compliance
 <b>Determination of water absorption</b>	EN ISO 10545-3-97	6,4 %	YES
 <b>Determination of flexion resistance and breaking load</b>	EN ISO 10545-4-97	R = 7,6 N/mm <sup>2</sup> (distance between supports = 180mm)	YES
 <b>Determination of chemical resistance</b>	EN ISO 10545-13-98	Class UA, ULA, UHA	YES
 <b>Determination of abrasion resistance</b>	Wide Disk Method	Print Length 28,0	YES
 <b>Determination of slip resistance</b>	UNE EN 12633	53 USRV	YES

NWT Cement Tiles, Cement Portland Class 3.

Test report, ELABORA - Agencia para la Calidad en la Construcción, S.L.

# Collection Overview

# Cement Tiles



6003.A



6003.B



6003.C



6003.D


OBELISCO




6000.A



6000.B




6000.C




6000.D

CENTINA




6004.A



6004.B



6004.C



6004.D

CAPITELLO



6005.A



6005.B



6005.C



6005.D

LUNETTA



6008.A



6008.B



6008.C



6008.D

ESEDRA



6002.A



6002.B



6002.C



6002.D

ARCO



6007.A



6007.B




6007.C



6007.D


ABSIDE



6006.A



6006.B




6006.C



6006.D


AGORA




6001.A



6001.B



6001.C



6001.D

ABACO

